EVACUUM UNIT





PHONE 03 5775 7300 EMAIL INFO@VACUUMTRUCKS.COM.AU WEBSITE WWW.VACUUMTRUCKS.COM.AU

EVACE 1600 SPECIFICATIONS



PORTABLE TOILET CLEANING



WASTE OIL



AND MUCH MORE!

Vacuum System

- Honda 5.5 HP petrol engine or Yanmar 6 HP diesel engine, both with electric starter motor
- 70 CFM Conde rotary vane vacuum pump
- · Belt driven with guard
- 12 V battery
- 50mm vacuum system
- All plumbing uses steel reinforced fuel suction hose with stainless steel clamps
- 75mm vacuum tank inlet including blockage removal port with camlock fitting
- 75mm discharge ball valve
- 10m of 50mm suction hose including ball valve and suction lance
- Primary shut off
- Secondary shut off with drain point
- Oil catch muffler with stainless steel filter and drain point

Vacuum Tank

- 1600 L waste capacity
- 5mm stainless steel barrel construction, skid mounted designed to be forked from four sides
- Tie down points
- Vacuum tank constructed to withstand 65 percent vacuum, no pressure capability
- 250mm wash out facility, 2 eyebolts and wing nuts to secure lid
- 810 KG empty weight
- Sight glasses to observe waste level in tank
- Dimensions: 2510mm L, 1370mm W, 1880mm H

Other Components

- 600 L water capacity with sight tube
- 12 V water pump 17 LPM flow 40 PSI pressure, manual on/off switch and water filter
- 18mm garden hose, 15m with spray nozzle
- Pressure relief valve
- Vacuum relief valve
- 65mm vacuum pressure gauge

ALSO AVAILABLE EVAC 800 AND EVAC 3200



PHONE 03 5775 7300 EMAIL INFO@VACUUMTRUCKS.COM.AU WEBSITE WWW.VACUUMTRUCKS.COM.AU